

## NAME

devprop - display device properties

## SYNOPSIS

/sbin/devprop [-n device-path] [-vq] [-{b|i|l|s}] [property[...]]

## DESCRIPTION

The devprop command displays named device properties from the device tree.

If a device path is specified on the command line, devprop displays device properties for that device node.

The output formats, while Volatile, are patterned after those of prtconf(1M).

## OPTIONS

The following options are supported:

-b

The properties to be output are sequences of bytes (DI\_PROP\_TYPE\_BYTES). -b, -i, -l, and -s are mutually exclusive of one another.

-i

The properties to be output are integers (DI\_PROP\_TYPE\_INT).

-l

The properties to be output are 64-bit integers (DI\_PROP\_TYPE\_INT64).

-s

The properties to be output are strings (DI\_PROP\_TYPE\_STRING) (the default).

-n device-path

The path to a target device node for which properties are displayed. The default path is that of the root node (equivalent to specifying -n /).

-q

Specifies quoted output mode, in which string properties are output surrounded by double quotation marks (").

-v

Specifies verbose mode, in which the name of the property is output before its value.

#### OPERANDS

The following operand is supported:

property...

Name of the property to be displayed.

#### EXIT STATUS

0

No error occurred.

non-zero

An error occurred.

#### ATTRIBUTES

See attributes(5) for descriptions of the following attributes:

ATTRIBUTE TYPE	ATTRIBUTE VALUE
Availability	SUNWcsr
Interface Stability	See below.

The command invocation and output are both Volatile. The location of the utility is Committed.

#### SEE ALSO

prtconf(1M), libdevinfo(3LIB), attributes(5)